


Technical Data Sheet		Belt type	NITTA BELT POLY LA-350NI2	NITTA CORPORATION  NITTA
Main uses	Stacker Belts for Printing Industry.			
No.	Item	Description		Remarks
1	Specification	Construction		①NBR (Orange Peel Pattern, Blue)
				②PA Fabric ③PA Film ④NBR (Orange Peel Pattern, Blue)
	Antistatic	Yes		
2	Dimensions	Width	5 to 300 {mm}	
		Length	300 to 100,000 {mm}	
		Thickness	1.35 {mm}	
		Joint	Skived joint Adhesive Polybond A and E	
3	Properties	Tensile strength	105 {N/mm}	Test speed: 50mm/min
		Elongation at break	20 {%}	Ambient condition: 23'C*50%
		Recommended elongation	2 {%}	
		Tension at 2%	5.2 {N/mm}	Ambient condition: 23'C*50%
		Minimum pulley dia.	25 {mm}	
		Temperature range	-20 to +80°C {°C}	
		Coefficient of friction	0.5 to 0.6(Steel) (Blue side)	Measuring condition: 7kPa*1mm/s
	0.5 to 0.6(Steel) (Blue side)	Ambient condition: 23'C*50%		
	Mass	1.55 {kg/m ² }		
4	Features			